

# INDUSTRIAL AIR COMPRESSORS



**NT-7580V**



**NT-7580H**

**Standard Features:**

- ✓ V-4 cylinder cast iron pump
- ✓ Low RPM for longer life
- ✓ Oil sight glass for rapid level checks
- ✓ Oil drain extension for easy oil changes
- ✓ Tapered roller bearings
- ✓ Ten individual concentric stainless steel disk valves
- ✓ Industrial motor, low speed
- ✓ Magnetic motor starter, mounted and wired, for all popular voltages.
- ✓ **Powder coated reservoir** for a brilliant and durable finish
- ✓ Factory tested, shipped with proper oil level and **READY TO WORK!**

**Options available:**

- WV-1: Automatic drain (installed)
- M-20: Air cooled aftercooler

**Voltages available : 230/1 phase, 208-230-460/3 phase, 575/3 phase**

SPECIFICATIONS										
Model Number	HP	Gal.	Pump	Cyl.	RPM	CFM @150	Dimensions (inches)			Weight (lbs)
							L	W	H	
NT-7580V	7.5	80	NT-10C	V-4	560	24.6	41	24	68	700
NT-7580H	7.5	80	NT-10C	V-4	560	24.6	63	20	44	725
NT-75120H	7.5	120	NT-10C	V-4	560	24.6	68	24	46	855

Due to continuing product improvement, specifications and features are subject to change.