

INDUSTRIAL AIR COMPRESSORS



NT-580V



NT-580H

Standard Features:

- ✓ V-4 cylinder cast iron pump
- ✓ Low RPM for longer life
- ✓ Oil sight glass for rapid level checks
- ✓ Oil drain extension for easy oil changes
- ✓ Tapered roller bearings
- ✓ Ten individual concentric stainless steel disk valves
- ✓ Industrial motor, low speed
- ✓ Magnetic motor starter, mounted and wired, for all popular voltages.
- ✓ **Powder coated reservoir** for a brilliant and durable finish
- ✓ Factory tested, shipped with proper oil level and **READY TO WORK!**

Options available:
WV-1: Automatic drain (installed)
M-20: Air cooled aftercooler

Voltages available : 230/1 phase, 230/3 phase, 575/3 phase

SPECIFICATIONS										
Model Number	HP	Gal.	Pump	Cyl.	RPM	CFM @150	Dimensions (inches)			Weight (lbs)
							L	W	H	
NT-580V	5	80	NT-10C	V-4	455	20.4	41	24	68	670
NT-580H	5	80	NT-10C	V-4	455	20.4	63	20	44	700
NT-5120H	5	120	NT-10C	V-4	455	20.4	68	25	46	820

Due to continuing product improvement, specifications and features are subject to change.

